

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1-3 (Canceled)

Claim 4 (Currently Amended) A rail mounted transportation system comprising

- a. a rail, and
- b. a support body, said support body comprising
  - 1. a load bearing section,
  - 2. a closest wheel between the rail and the load bearing section, and
  - 3. a furthest wheel placed at a fixed distance from the closest wheel and separated from the closest wheel by the rail;
- c. wherein said closest wheel is adapted to operate as a fulcrum with respect to a weight of said ~~support body~~ load bearing section on one side thereof, and the furthest wheel to an opposite side thereof; and
- d. wherein the furthest wheel is adapted to transfer, in response to a rotation weight of the load bearing section urging the support body to pivot about said fulcrum-is terminated , an upward force to a lower side of the rail by contact between said furthest wheel and said lower side of the rail; and
- e. ~~wherein a magnitude of said rotation is relative to a gauge of said rail.~~

Claims 5 (Canceled)

Claim 6 (New) A rail mounted transportation system comprising

- a. a rail, and
- b. a support body, said support body comprising
  - 1. an upper wheel,
  - 2. a lower wheel separated from the upper wheel by the rail, and
  - 3. a load bearing section

wherein the rail has a first inclined portion and a less inclined portion, in which the first inclined portion has a steeper slope than the less inclined portion, and

wherein further the rail is thicker in vertical measurement at the first inclined portion than it is at the less inclined portion.

Claim 7 (New) A rail mounted transportation system as in Claim 6, wherein the load bearing section is closer to the upper wheel than to the lower wheel.

Claim 8 (New) A rail mounted transportation system as in Claim 6, wherein at least a part of the load bearing section is directly over a downslope side of the rail.

Claim 9 (New) A rail mounted transportation system as in Claim 6, wherein there is a fixed angle between the load bearing section and a line drawn between the upper wheel and the lower wheel.

Claim 10 (New) A rail mounted transportation system comprising

- a. a rail, and
- b. a support body, said support body comprising
  - 1. an upper wheel,
  - 2. a lower wheel separated from the upper wheel by the rail, and
  - 3. a load bearing section

wherein the rail has a greater inclined portion and a lesser inclined portion, in which the greater inclined portion has a steeper slope than the lesser inclined portion, and wherein an orientation, relative to the rail, of a line drawn between an axis of the upper wheel and an axis of the lower wheel, approaches perpendicular as a slope of the rail increases.